



Draka

Type RHH / RHW-2 / USE-2 XLPE Insulated Wire

Single conductor / 14 AWG to 500 KCMIL / 600V



Applications

Draka's Type RHH/RHW-2/USE-2 cable is suitable for various commercial and industrial applications. These cables may be installed in wet or dry locations, indoors or outdoors, in raceways, underground ducts (ask about our preinstalled cable-in-conduit products), aerial or direct buried.

Draka's Type RHH/RHW-2/USE-2 cable is NEC-compliant for continuous operations at 90° C in wet and dry locations, 130° C for emergency overload conditions and 250° C for short circuit conditions.

Features

1. CONDUCTORS

Class B, soft drawn, bare copper per ASTM B3 and ASTM B8. Both tinned copper conductors and extra-flexible conductors are available as options.

2. INSULATION

Heat and moisture resistant crosslinked polyethylene (XLPE) meeting the requirements ICEA S-95-658 (NEMA WC 70), UL 44 for Type RHH and RHW-2 wires and UL 854 for Type USE-2. The insulation is suitable for use in wet or dry locations at a conductor temperature not exceeding 90° C for normal operation.

3. ASSEMBLY

Single conductor cables can be paralleled or multiplexed for more efficient installations. Single conductor cables can also be pre-installed in conduit.

Ratings

UL Type RHH or RHW-2 or USE-2

The insulation is suitable for use in wet or dry locations at a temperature not exceeding 90° C -40° C rated

Direct burial

Sunlight resistant

Oil & gas resistant II

FT2

VW-1 CT USE (#1/0 AWG and larger) constructions are available

RoHS compliant



Type RHH / RHW-2 / USE-2 XLPE Insulated Wire

Single conductor / 14 AWG to 500 KCMIL / 600V

Conductor Size AWG (mm ²)	Strand Class	Strands	Nominal Insulation Thickness in (mm)	Nominal Cable O.D. in (mm)	Approximate Cable Weight Lbs/Mft (Kg/Km)
14 AWG (2.08)	Class B	7	.045 (1.1)	0.170 (4.3)	22 (33)
12 AWG (3.31)	Class B	7	.045 (1.1)	0.190 (4.8)	30 (45)
10 AWG (5.26)	Class B	7	.045 (1.1)	0.215 (5.5)	44 (65)
8 AWG (8.37)	Class B	7	.060 (1.5)	0.275 (7.0)	72 (107)
6 AWG (13.3)	Class B	7	.060 (1.5)	0.310 (7.9)	106 (158)
4 AWG (21.2)	Class B	7	.060 (1.5)	0.360 (9.1)	160 (238)
2 AWG (33.6)	Class B	7	.060 (1.5)	0.420 (10.7)	243 (362)
1 AWG (42.4)	Class B	19	.080 (2.0)	0.500 (12.7)	311 (463)
1/0 AWG (53.5)	Class B	19	.080 (2.0)	0.540 (13.7)	387 (576)
2/0 AWG (67.4)	Class B	19	.080 (2.0)	0.585 (14.9)	492 (732)
3/0 AWG (85.0)	Class B	19	.080 (2.0)	0.635 (16.1)	611 (909)
4/0 AWG (107)	Class B	19	.080 (2.0)	0.695 (17.7)	740 (1101)
250 KCMIL (127)	Class B	37	.095 (2.4)	0.770 (19.6)	882 (1312)
350 KCMIL (177)	Class B	37	.095 (2.4)	0.875 (22.2)	1213 (1805)
500 KCMIL (253)	Class B	37	.095 (2.4)	1.005 (25.5)	1702 (2533)

These cables are made in the USA, meeting ISO 9001 Quality Standard & 14001 Environmental Standard.

The data herein is approximate and subject to normal manufacturing tolerances. These specifications are subject to change without notice.

Draka Engineered Specialties

22 Joseph E. Warner Blvd. | North Dighton, MA 02764 | Tel +1-508-822-5444
 761 Joseph E. Warner Blvd. | Taunton, MA 02780 | Tel +1-508-822-5444
 One Tamaqua Blvd. | Schuylkill Haven PA 17972 | Tel +1-570-385-4381

For sales and technical information, contact:

Draka Engineered Specialties | 1-800-233-3190 | 1-570-385-4381 | 1-570-385-1092 fax | www.drakausa.com